

Overview



HP ProCurve Switch 3500yl-24G-PWR Intelligent Edge



HP ProCurve Switch 3500yl-48G-PWR Intelligent Edge

Models

| | |
|--|--------|
| HP ProCurve Switch 3500yl-24G-PWR Intelligent Edge | J8692A |
| HP ProCurve Switch 3500yl-48G-PWR Intelligent Edge | J8693A |
| HP ProCurve 3500-24 Switch | J9470A |
| HP ProCurve 3500-24-PoE Switch | J9471A |
| HP ProCurve 3500-48 Switch | J9472A |
| HP ProCurve 3500-48-PoE Switch | J9473A |

Key features

- Advanced access layer & Small Distribution
- Enterprise-class performance and security
- Intelligent Edge feature set with L2-L4
- Scalable 10/100/1000 & 10/100 PoE connectivity
- Unified core-to-edge ProVision software

Introduction

The HP ProCurve Switch 3500 Series consists of the most advanced intelligent edge switches in the HP ProCurve Networking product line. The 3500 series includes 24-port and 48-port stackables. The foundation for all these switches is a purpose-built, programmable ProVision ASIC that allows the most demanding networking features, such as Quality of Service (QoS) and security, to be implemented in a scalable yet granular fashion. With a variety of Gigabit and 10/100 interfaces, integrated PoE and Non-PoE options, 10-GbE capability on Gigabit switches, the 3500 switches offer excellent investment protection, flexibility, and scalability, as well as ease of deployment, operation, and maintenance.

Features and Benefits

Industry-leading warranty*

Management

- **Remote Intelligent Mirroring:** mirrors selected ingress/egress traffic based on ACL, port, MAC address, or VLAN to a local or remote 8200zl/6600/6200yl/5400zl/3500 switch anywhere on the network
- **RMON, XRMON, and sFlow v5:** provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol for easy mapping by network management applications
- **Uni-Directional Link Detection (UDLD):** monitors cable between two switches and shuts down the ports on both ends if the cable is broken turning the bi-directional link into uni-directional; this prevents network problems such as loops
- **Management simplicity:** ProCurve-common networking features and CLI implementation (common across ProCurve 8200zl/6600/6200yl/5400zl/3500 switches)
- **Command authorization:** leverages RADIUS to link a custom list of CLI commands to individual network administrator's login; also provides an audit trail
- **Friendly port names:** allow assignment of descriptive names to ports
- **Dual flash images:** provides independent primary and secondary OS files for backup while upgrading
- **Multiple configuration files:** multiple configuration files can be stored to the flash image

Overview

Connectivity

- **NEW IPv6:**
 - **IPv6 host:** the switches can be managed and deployed at the edge of IPv6 networks
 - **Dual stack (IPv4/IPv6):** provides transition mechanism from IPv4 to IPv6; supports connectivity for both protocols
 - **MLD snooping:** forwards IPv6 multicast traffic to the appropriate interface; prevents IPv6 multicast traffic from flooding the network
 - **IPv6 ACL/QoS:** supports ACL and QoS for IPv6 network traffic
 - **IPv6 ready:** the switch hardware can support IPv6 routing, tunneling, and security; these features will be available when enabled via software update in follow-on releases
- **IEEE 802.3af Power over Ethernet:** provides up to 15.4 W per port to IEEE 802.3af-compliant PoE powered devices such as IP phones, wireless access points, and security cameras
- **Pre-standard PoE support:** detects and provides power to pre-standard PoE devices; see list of supported devices in the product FAQ at www.procurve.com
- **Jumbo frames:** on Gigabit and 10-Gigabit ports, allow high-performance remote backup and disaster-recovery services
- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100 and 10/100/1000 ports

Performance

- **High-speed/capacity architecture:** up to 153.6 Gbps crossbar switching fabric provides intra- and inter- module switching with up to 111.5 million pps throughput on the purpose-built ProVision ASICs
- **Selectable queue configurations:** increase performance by selecting the number of queues and associated memory buffering that best meet the requirements of your network applications

Resiliency and high availability

- **Virtual Router Redundancy Protocol** (requires Premium License): VRRP allows groups of two routers to dynamically back each other up to create highly available routed environments
- **IEEE 802.1s Multiple Spanning Tree Protocol:** provides high link availability in multiple VLAN environments by allowing multiple spanning trees; encompasses IEEE 802.1D Spanning Tree Protocol and IEEE 802.1w Rapid Spanning Tree Protocol
- **NEW Server-to-switch distributed trunking:** allows a server to connect to two switches with one logical trunk that consists of multiple physical connections; enables load-balancing and increases resiliency
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP) and ProCurve trunking:** support up to 60 trunks, each with up to 8 links (ports) per trunk

Layer 2 switching

- **IEEE 802.1ad Q-in-Q** (requires Premium License): increases the scalability of Ethernet network by providing a hierarchical structure; connects multiple LANs on high-speed campus or metro network
- **ProCurve switch meshing:** dynamically load-balances across multiple active redundant links to increase available aggregate bandwidth
- **VLAN support and tagging:** supports the IEEE 802.1Q standard and 2,048 VLANs simultaneously
- **IEEE 802.1v protocol VLANs:** isolate select non-IPv4 protocols automatically into their own VLANs
- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs

Layer 3 services

- **UDP helper function:** UDP broadcasts can be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevent server spoofing for UDP services such as DHCP
- **Loopback interface address:** defines an address in RIP and OSPF that can always be reachable, improving diagnostic capability

Layer 3 routing

- **Static IP routing:** provides manually configured routing; includes ECMP capability
- **RIP:** provides RIPv1 and RIPv2 routing



Overview

- **OSPF** (requires Premium License): includes host-based ECMP to provide link redundancy/scalable bandwidth and NSSA

Security

- **Access control lists (ACLs)**: provide filtering based on the IP field, source/destination IP address/subnet, and source/destination TCP/UDP port number on a per-VLAN or per-port basis
- **Multiple user authentication methods**:
 - **IEEE 802.1X users per port**: provides authentication of multiple IEEE 802.1X users per port; prevents user “piggybacking” on another user’s IEEE 802.1X authentication
 - **Web-based authentication**: authenticates from Web browser for clients that do not support IEEE 802.1X supplicant; customized remediation can be processed on an external Web server
 - **MAC-based authentication**: client is authenticated with the RADIUS server based on client’s MAC address
 - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port**: switch port will accept up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **Virus throttling**: detects traffic patterns typical of WORM-type viruses and either throttles or entirely prevents the ability of the virus to spread across the routed VLANs or bridged interfaces, without requiring external appliances
- **DHCP protection**: blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Secure management access**: all access methods—CLI, GUI, or MIB—are securely encrypted through SSHv2, SSL, and/or SNMPv3
- **USB Secure Autorun** (requires HP ProCurve Manager Plus): deploys, diagnoses, and updates switch using USB flash drive; works with secure credential to prevent tampering
- **Switch CPU protection**: provides automatic protection against malicious network traffic trying to shut down the switch
- **ICMP throttling**: defeats ICMP denial-of-service attacks by enabling any switch port to automatically throttle ICMP traffic
- **Identity-driven ACL**: enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **STP BPDU port protection**: blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **Dynamic IP lockdown**: works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **Dynamic ARP protection**: blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **STP Root Guard**: protects root bridge from malicious attack or configuration mistakes
- **Detection of malicious attacks**: monitors ten types of network traffic and sends a warning when an anomaly that potentially can be caused by malicious attacks is detected
- **Port security**: allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout**: prevents configured particular MAC addresses from connecting to the network
- **Source-port filtering**: allows only specified ports to communicate with each other
- **RADIUS/TACACS+**: eases switch management security administration by using a password authentication server
- **Secure Shell (SSHv2)**: encrypts all transmitted data for secure, remote command-line interface (CLI) access over IP networks
- **Secure Sockets Layer (SSL)**: encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Secure FTP**: allows secure file transfer to/from the switch; protects against unwanted file downloads or unauthorized copying of switch configuration file
- **NEW Management Interface Wizard**: CLI-based step-by-step configuration tool to help ensure that management interfaces such as SNMP, telnet, SSH, SSL, Web, and USB are secured to desired level
- **Switch management logon security**: can require either RADIUS or TACACS+ authentication for secure switch CLI logon
- **Security banner**: displays a customized security policy when users log in to the switch

Convergence

- **IP multicast routing** (requires Premium License): includes PIM Sparse and Dense modes to route IP multicast traffic
- **IP multicast snooping** (data-driven IGMP): automatically prevents flooding of IP multicast traffic
- **LLDP-MED** (Media Endpoint Discovery): a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones

Overview

- **RADIUS VLAN for voice:** uses standard RADIUS attribute and LLDP-MED to automatically configure VLAN for IP phones
- **PoE allocations:** supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user specified) to allocate PoE power for more efficient energy savings

Quality of Service (QoS)

- **NEW Advanced classifier-based QoS:** classifies traffic using multiple match criteria based on L2/3/4 information; applies QoS policies such as setting priority level and rate limit to selected traffic per port or per VLAN
- **Layer 4 prioritization:** enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization:** allows real-time traffic classification into eight priority levels mapped to eight queues
- **Bandwidth shaping:**
 - **Port-based rate limiting:** per-port ingress/egress enforced maximum bandwidth
 - **Classifier-based rate limiting:** use ACL to enforce maximum bandwidth for ingress traffic on each port
 - **Guaranteed minimum:** per-port, per-queue egress-based guaranteed minimum bandwidth
- **Class of Service (CoS):** sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), L3 protocol, TCP/UDP port number, source port, and DiffServ

Warranty and support*

- **ProCurve Lifetime Warranty:** for as long as you own the product, with next-business-day advance replacement (available in most countries).
- **Electronic and telephone support:** limited electronic and telephone support is available from HP. Refer to the HP Web site at: www.procurve.com/support for details on the support provided and the period during which support is available.
- **Software releases:** refer to the HP Web site at: www.procurve.com/support for details on the software releases provided and the period during which software releases are available.

* For as long as you own the product, with next-business-day advance replacement (available in most countries). The following hardware products and their related series modules have a one-year hardware warranty with extensions available: HP ProCurve Routing Switch 9300m Series, HP ProCurve Switch 8100fl Series, HP ProCurve Network Access Controller 800, and HP ProCurve DCM Controller. The following hardware mobility products have a one-year hardware warranty with extensions available: HP ProCurve M111 Client Bridge, HP ProCurve MSM3xx-R Access Points, HP ProCurve MSM7xx Mobility and Access Controllers, HP ProCurve RF Manager IDS/IPS Systems, HP ProCurve MSM Power Supplies, HP ProCurve 1-Port Power Injector, and HP ProCurve CNMS Appliances. Disk drives in the HP ProCurve ONE Services zl Modules have a five year hardware warranty. Standalone software, upgrades, or licenses may have a different warranty duration. For details, refer to the ProCurve Software License, Warranty, and Support booklet at: www.procurve.com/warranty.

Technical Specifications

| | | |
|--|-----------------------------------|---|
| HP ProCurve Switch 3500yl-24G-PWR Intelligent Edge (J8692A) | Ports | 1 open module slot 20 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Media Type: Auto-MDIX; Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only 1 RS-232C DB-9 console port 4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) with PoE or an open mini-GBIC slot (for use with mini-GBIC transceivers) |
| | Physical characteristics | Maximum ports Supports a maximum of 4 10-GbE ports Dimensions 15.43(d) x 17.44(w) x 1.73(h) in. (39.2 x 44.3 x 4.4 cm) (1U height) Weight 14.11 lb. (6.4 kg) |
| | Memory and processor | 10G module ARM9 @ 200 MHz; packet buffer size: 36 Mb QDR SDRAM Management Module Stackable memory and processor: Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM |
| | Mounting | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only |
| | Performance | Latency 1000 Mb: < 3.7 μs (FIFO 64-byte packets); 10 Gbps: < 2.1 μs (FIFO 64-byte packets) Throughput up to 75.7 million pps Routing/Switching capacity 101.8 Gbps Switch fabric speed 105.6 Gbps Routing table size 10,000 entries MAC address table size 64,000 entries |
| | Environment | Operating temperature 32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when used with any X2 10-GbE Operating relative humidity 15% to 95% @ 104°F (40°C), non-condensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 15% to 90% @ 149°F (65°C), non-condensing Altitude up to 15,000 ft. (4.6 km) Acoustic Power: 52.7 dB, Pressure: 44.8 dB ISO 7779, ISO 9296 |
| | Electrical characteristics | Description The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz Maximum heat dissipation 865 BTU/hr (912.9 kJ/hr) Voltage 100-127 / 200-240 VAC Current 10.0 / 5.0 A Idle power 98 W Maximum power rating 623 W |

Technical Specifications

| | | |
|--------------------------------|---------------------------------------|---|
| | PoE power | 398 W |
| | Frequency | 50 / 60 Hz |
| | Notes | Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS). |
| Safety | | CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950 |
| Emissions | | FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A |
| Immunity | EN | EN 55024, CISPR 24 |
| | ESD | IEC 61000-4-2; 4 kV CD, 8 kV AD |
| | Radiated | IEC 61000-4-3; 3 V/m |
| | EFT/Burst | IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) |
| | Surge | IEC 61000-4-5; 1 kV/2 kV AC |
| | Conducted | IEC 61000-4-6; 3 V |
| | Power frequency magnetic field | IEC 61000-4-8; 1 A/m, 50 or 60 Hz |
| | Voltage dips and interruptions | IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods |
| | Harmonics | EN 61000-3-2, IEC 61000-3-2 |
| | Flicker | EN 61000-3-3, IEC 61000-3-3 |
| Management | | HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C) |
| Notes | | When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. |
| Services | | Refer to the HP Web site at: www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |
| Standards and protocols | Device Management | RFC 1591 DNS (client) HTML and telnet management |
| | General Protocols | IEEE 802.1ad Q-in-Q (Premium License) IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) |

Technical Specifications

| | |
|---------------------|--|
| | IEEE 802.3af Power over Ethernet |
| | IEEE 802.3x Flow Control |
| | RFC 768 UDP |
| | RFC 783 TFTP Protocol (revision 2) |
| | RFC 792 ICMP |
| | RFC 793 TCP |
| | UDLD (Uni-directional Link Detection) |
| | RFC 826 ARP |
| | RFC 854 TELNET |
| | RFC 868 Time Protocol |
| | RFC 951 BOOTP |
| | RFC 1058 RIPv1 |
| | RFC 1350 TFTP Protocol (revision 2) |
| | RFC 1519 CIDR |
| | RFC 1542 BOOTP Extensions |
| | RFC 2030 Simple Network Time Protocol (SNTP) v4 |
| | RFC 2131 DHCP |
| | RFC 2453 RIPv2 |
| | RFC 2548 (MS-RAS-Vendor only) |
| | RFC 3046 DHCP Relay Agent Information Option |
| | RFC 3576 Ext to RADIUS (CoA only) |
| | RFC 3768 VRRP (Premium License) |
| | RFC 4675 RADIUS VLAN & Priority |
| IP Multicast | RFC 3376 IGMPv3 (host joins only) |
| | RFC 3973 Draft 2 PIM Dense Mode (Premium License) |
| | RFC 4601 Draft 10 PIM Sparse Mode (Premium License) |
| IPv6 | RFC 1981 IPv6 Path MTU Discovery |
| | RFC 2460 IPv6 Specification |
| | RFC 2710 Multicast Listener Discovery (MLD) for IPv6 |
| | RFC 2925 Remote Operations MIB (Ping only) |
| | RFC 3019 MLDv1 MIB |
| | RFC 3315 DHCPv6 (client only) |
| | RFC 3513 IPv6 Addressing Architecture |
| | RFC 3596 DNS Extension for IPv6 |
| | RFC 3810 MLDv2 (host joins only) |
| | RFC 4022 MIB for TCP |
| | RFC 4113 MIB for UDP |
| | RFC 4251 SSHv6 Architecture |
| | RFC 4252 SSHv6 Authentication |
| | RFC 4253 SSHv6 Transport Layer |
| | RFC 4254 SSHv6 Connection |
| | RFC 4293 MIB for IP |
| | RFC 4419 Key Exchange for SSH |
| | RFC 4443 ICMPv6 |
| | RFC 4541 IGMP & MLD Snooping Switch |
| | RFC 4861 IPv6 Neighbor Discovery |
| | RFC 4862 IPv6 Stateless Address Auto-configuration |
| MIBs | RFC 1213 MIB II |
| | RFC 1493 Bridge MIB |
| | RFC 1724 RIPv2 MIB |

Technical Specifications

| | |
|---------------------------|---|
| | RFC 1850 OSPFv2 MIB |
| | RFC 2021 RMONv2 MIB |
| | RFC 2096 IP Forwarding Table MIB |
| | RFC 2613 SMON MIB |
| | RFC 2618 RADIUS Client MIB |
| | RFC 2620 RADIUS Accounting MIB |
| | RFC 2665 Ethernet-Like-MIB |
| | RFC 2668 802.3 MAU MIB |
| | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| | RFC 2737 Entity MIB (Version 2) |
| | RFC 2787 VRRP MIB |
| | RFC 2863 The Interfaces Group MIB |
| | RFC 2925 Ping MIB |
| Network Management | IEEE 802.1AB Link Layer Discovery Protocol (LLDP) |
| | RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) |
| | RFC 3176 sFlow |
| | ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) |
| | SNMPv1/v2c/v3 |
| | XRMON |
| OSPF | RFC 2328 OSPFv2 (Premium License) |
| | RFC 3101 OSPF NSSA |
| QoS/Cos | RFC 2474 DiffServ Precedence, including 8 queues/port |
| | RFC 2597 DiffServ Assured Forwarding (AF) |
| | RFC 2598 DiffServ Expedited Forwarding (EF) |
| Security | IEEE 802.1X Port Based Network Access Control |
| | RFC 1492 TACACS+ |
| | RFC 2865 RADIUS (client only) |
| | RFC 2866 RADIUS Accounting |
| | Secure Sockets Layer (SSL) |
| | SSHv1/SSHv2 Secure Shell |

| | | |
|--|---------------------------------|---|
| HP ProCurve Switch 3500yl-48G-PWR Intelligent Edge (J8693A) | Ports | 1 open module slot 44 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Media Type: Auto-MDIX; Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only 1 RS-232C DB-9 console port 4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) with PoE or an open mini-GBIC slot (for use with mini-GBIC transceivers) |
| | Physical characteristics | Maximum ports Supports a maximum of 4 10-GbE ports Dimensions 16.93(d) x 17.44(w) x 1.73(h) in. (43.0 x 44.3 x 4.4 cm) (1U height) Weight 16.09 lb. (7.3 kg) |

Technical Specifications

| | | |
|---|--|--|
| Memory and processor | 10G module | ARM9 @ 200 MHz; packet buffer size: 36 Mb QDR SDRAM |
| | Management Module | Stackable memory and processor: Freescale PowerPC 8540 @ 666 MHz, 4 MB flash Mb, 128 MB compact flash, 256 MB DDR SDRAM |
| Mounting | | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only |
| Performance | Latency | 1000 Mb: < 3.7 μ s (FIFO 64-byte packets); 10 Gbps: < 2.1 μ s (FIFO 64-byte packets) |
| | Throughput | up to 111.5 million pps |
| | Routing/Switching capacity | 149.8 Gbps |
| | Switch fabric speed | 153.6 Gbps |
| | Routing table size | 10,000 entries |
| | MAC address table size | 64,000 entries |
| Environment | Operating temperature | 32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when used with any X2 10-GbE |
| | Operating relative humidity | 15% to 95% @ 104°F (40°C), non-condensing |
| | Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| | Non-operating/Storage relative humidity | 15% to 95% @ 149°F (65°C), non-condensing |
| | Altitude | up to 15,000 ft. (4.6 km) |
| | Acoustic | Power: 55.1 dB, Pressure: 45.3 dB ISO 7779, ISO 9296 |
| Electrical characteristics (Achieved Miercom Certified Green Award) | Description | The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz |
| | Maximum heat dissipation | 1144 BTU/hr (1206.9 kJ/hr) |
| | Voltage | 100-127 / 200-240 VAC |
| | Current | 10.0 / 5.0 A |
| | Idle power | 142 W |
| | Maximum power rating | 705 W |
| | PoE power | 398 W |
| | Frequency | 50 / 60 Hz |
| | Notes | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. Maximum power draw if not using any PoE power is 200 W (1.8 A @ 110 V, 0.9 A @ 220 V). Full load switch only heat spec listed above subtracts heat dissipated in external PoE powered devices. Heat dissipation does not include heat dissipated by the PoE powered devices themselves. |
| Safety | | CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950 |

Technical Specifications

| | |
|--------------------------------|---|
| Emissions | FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A |
| Immunity | EN EN 55024, CISPR 24 |
| | ESD IEC 61000-4-2; 4 kV CD, 8 kV AD |
| | Radiated IEC 61000-4-3; 3 V/m |
| | EFT/Burst IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) |
| | Surge IEC 61000-4-5; 1 kV/2 kV AC |
| | Conducted IEC 61000-4-6; 3 V |
| | Power frequency magnetic field IEC 61000-4-8; 1 A/m, 50 or 60 Hz |
| | Voltage dips and interruptions IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods |
| | Harmonics EN 61000-3-2, IEC 61000-3-2 |
| | Flicker EN 61000-3-3, IEC 61000-3-3 |
| Management | HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C) |
| Notes | When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. |
| Services | Refer to the HP Web site at: www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |
| Standards and protocols | <p>Device Management RFC 1591 DNS (client) HTML and telnet management</p> <p>General Protocols IEEE 802.1ad Q-in-Q (Premium License) IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP UDLD (Uni-directional Link Detection) RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4</p> |

| | |
|---------------------------|--|
| | RFC 2131 DHCP |
| | RFC 2453 RIPv2 |
| | RFC 2548 (MS-RAS-Vendor only) |
| | RFC 3046 DHCP Relay Agent Information Option |
| | RFC 3576 Ext to RADIUS (CoA only) |
| | RFC 3768 VRRP (Premium License) |
| | RFC 4675 RADIUS VLAN & Priority |
| IP Multicast | RFC 3376 IGMPv3 (host joins only) |
| | RFC 3973 Draft 2 PIM Dense Mode (Premium License) |
| | RFC 4601 Draft 10 PIM Sparse Mode (Premium License) |
| IPv6 | RFC 1981 IPv6 Path MTU Discovery |
| | RFC 2460 IPv6 Specification |
| | RFC 2710 Multicast Listener Discovery (MLD) for IPv6 |
| | RFC 2925 Remote Operations MIB (Ping only) |
| | RFC 3019 MLDv1 MIB |
| | RFC 3315 DHCPv6 (client only) |
| | RFC 3513 IPv6 Addressing Architecture |
| | RFC 3596 DNS Extension for IPv6 |
| | RFC 3810 MLDv2 (host joins only) |
| | RFC 4022 MIB for TCP |
| | RFC 4113 MIB for UDP |
| | RFC 4251 SSHv6 Architecture |
| | RFC 4252 SSHv6 Authentication |
| | RFC 4253 SSHv6 Transport Layer |
| | RFC 4254 SSHv6 Connection |
| | RFC 4293 MIB for IP |
| | RFC 4419 Key Exchange for SSH |
| | RFC 4443 ICMPv6 |
| | RFC 4541 IGMP & MLD Snooping Switch |
| | RFC 4861 IPv6 Neighbor Discovery |
| | RFC 4862 IPv6 Stateless Address Auto-configuration |
| MIBs | RFC 1213 MIB II |
| | RFC 1493 Bridge MIB |
| | RFC 1724 RIPv2 MIB |
| | RFC 1850 OSPFv2 MIB |
| | RFC 2021 RMONv2 MIB |
| | RFC 2096 IP Forwarding Table MIB |
| | RFC 2613 SMON MIB |
| | RFC 2618 RADIUS Client MIB |
| | RFC 2620 RADIUS Accounting MIB |
| | RFC 2665 Ethernet-Like-MIB |
| | RFC 2668 802.3 MAU MIB |
| | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| | RFC 2737 Entity MIB (Version 2) |
| | RFC 2787 VRRP MIB |
| | RFC 2863 The Interfaces Group MIB |
| | RFC 2925 Ping MIB |
| Network Management | IEEE 802.1AB Link Layer Discovery Protocol (LLDP) |
| | RFC 2819 Four groups of RMON: 1 |

Technical Specifications

| | |
|-----------------|---|
| | (statistics), 2 (history), 3 (alarm) and 9 (events) |
| | RFC 3176 sFlow |
| | ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) |
| | SNMPv1/v2c/v3 |
| | XRMON |
| OSPF | RFC 2328 OSPFv2 (Premium License) RFC 3101 OSPF NSSA |
| QoS/Cos | RFC 2474 DiffServ Precedence, including 8 queues/port RFC 2597 DiffServ Assured Forwarding (AF) RFC 2598 DiffServ Expedited Forwarding (EF) |
| Security | IEEE 802.1X Port Based Network Access Control RFC 1492 TACACS+ RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting Secure Sockets Layer (SSL) SSHv1/SSHv2 Secure Shell |

| | | |
|--|---------------------------------|---|
| HP ProCurve 3500-24 Switch (J9470A) | Ports | 20 RJ-45 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Media Type: Auto-MDIX; Duplex: half or full |
| | | 4 dual-personality ports; Each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers) |
| | | 1 RS-232C DB-9 console port |
| | Physical characteristics | Dimensions 15.43(d) x 17.44(w) x 1.73(h) in. (39.2 x 44.3 x 4.4 cm) (1U height) |
| | | Weight 11.9 lb. (5.4 kg) |
| | Memory and processor | 10G module |
| | | Management Module Stackable memory and processor: Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM |
| | Mounting | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only |
| | Performance | Latency 100 Mb: < 3.4 μs (FIFO 64-byte packets); 1000 Mb: < 2.9 μs (FIFO 64-byte packets) |
| | | Throughput up to 8.9 million pps (64-byte packets) |
| | | Routing/Switching capacity 12 Gbps |
| | | Switch fabric speed |
| | | Routing table size 10,000 entries |
| | | MAC address table size 64,000 entries |
| | Environment | Operating temperature 32°F to 131°F (0°C to 55°C) |
| | | Operating relative humidity 15% to 95% @ 104°F (40°C), non-condensing |



Technical Specifications

| | | |
|---------------------------------------|---|---|
| | Non-operating/ Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| | Non-operating/ Storage relative humidity | 15% to 95% @ 149°F (65°C), non-condensing |
| | Altitude | up to 15,000 ft. (4.6 km) |
| | Acoustic | Power: 52.7 dB, Pressure: 44.8 dB ISO 7779, ISO 9296 |
| Electrical characteristics | Description | The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz |
| | Maximum heat dissipation | 268 BTU/hr (282.8 kJ/hr) |
| | Voltage | 100-127 / 200-240 VAC |
| | Current | 1.1 / 0.6 A |
| | Idle power | 68.2 W |
| | Maximum power rating | 78.7 W |
| | PoE power | |
| | Frequency | 50 / 60 Hz |
| | Notes | Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| | Safety Emissions Immunity | |
| | | FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A |
| EN | | EN 55024, CISPR 24 |
| ESD | | IEC 61000-4-2; 4 kV CD, 8 kV AD |
| Radiated | | IEC 61000-4-3; 3 V/m |
| EFT/Burst | | IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) |
| Surge | | IEC 61000-4-5; 1 kV/2 kV AC |
| Conducted | | IEC 61000-4-6; 3 V |
| Power frequency magnetic field | | IEC 61000-4-8; 1 A/m, 50 or 60 Hz |
| Voltage dips and interruptions | | IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods |
| Management | Harmonics | EN 61000-3-2, IEC 61000-3-2 |
| | Flicker | EN 61000-3-3, IEC 61000-3-3 |
| | | HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C) |
| Notes | When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. | |
| Services | 3-year, 4-hour onsite, 13x5 coverage for hardware (U2855E) 3-year, 4-hour onsite, 24x7 coverage for hardware (U2856E) | |

Technical Specifications

3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6304E)
3-year, 24x7 SW phone support, software updates (UE262E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UR868E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UR869E)
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR870E)
4-year, 24x7 SW phone support, software updates (UR871E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UR872E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UR873E)
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR874E)
5-year, 24x7 SW phone support, software updates (UR875E)
Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

Device Management RFC 1591 DNS (client)
HTML and telnet management

General Protocols IEEE 802.1ad Q-in-Q (Premium License)
IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1v VLAN classification by Protocol and Port
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3af Power over Ethernet
IEEE 802.3x Flow Control
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 792 ICMP
RFC 793 TCP
UDLD (Uni-directional Link Detection)
RFC 826 ARP
RFC 854 TELNET
RFC 868 Time Protocol
RFC 951 BOOTP
RFC 1058 RIPv1
RFC 1350 TFTP Protocol (revision 2)
RFC 1519 CIDR
RFC 1542 BOOTP Extensions
RFC 2030 Simple Network Time Protocol (SNTP) v4
RFC 2131 DHCP
RFC 2453 RIPv2
RFC 2548 (MS-RAS-Vendor only)
RFC 3046 DHCP Relay Agent Information Option
RFC 3576 Ext to RADIUS (CoA only)
RFC 3768 VRRP (Premium License)
RFC 4675 RADIUS VLAN & Priority

Technical Specifications

| | |
|---------------------------|---|
| IP Multicast | RFC 3376 IGMPv3 (host joins only) RFC 3973 Draft 2 PIM Dense Mode (Premium License) RFC 4601 Draft 10 PIM Sparse Mode (Premium License) |
| IPv6 | RFC 1981 IPv6 Path MTU Discovery RFC 2460 IPv6 Specification RFC 2710 Multicast Listener Discovery (MLD) for IPv6 RFC 2925 Remote Operations MIB (Ping only) RFC 3019 MLDv1 MIB RFC 3315 DHCPv6 (client only) RFC 3513 IPv6 Addressing Architecture RFC 3596 DNS Extension for IPv6 RFC 3810 MLDv2 (host joins only) RFC 4022 MIB for TCP RFC 4113 MIB for UDP RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication RFC 4253 SSHv6 Transport Layer RFC 4254 SSHv6 Connection RFC 4293 MIB for IP RFC 4419 Key Exchange for SSH RFC 4443 ICMPv6 RFC 4541 IGMP & MLD Snooping Switch RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration |
| MIBs | RFC 1213 MIB II RFC 1493 Bridge MIB RFC 1724 RIPv2 MIB RFC 1850 OSPFv2 MIB RFC 2021 RMONv2 MIB RFC 2096 IP Forwarding Table MIB RFC 2613 SMON MIB RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2737 Entity MIB (Version 2) RFC 2787 VRRP MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB |
| Network Management | IEEE 802.1AB Link Layer Discovery Protocol (LLDP) RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) RFC 3176 sFlow ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3 XRMON |

Technical Specifications

| | | |
|--|-----------------|---|
| | OSPF | RFC 2328 OSPFv2 (Premium License) RFC 3101 OSPF NSSA |
| | QoS/Cos | RFC 2474 DiffServ Precedence, including 8 queues/port RFC 2597 DiffServ Assured Forwarding (AF) RFC 2598 DiffServ Expedited Forwarding (EF) |
| | Security | IEEE 802.1X Port Based Network Access Control RFC 1492 TACACS+ RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting Secure Sockets Layer (SSL) SSHv1/SSHv2 Secure Shell |

| | | |
|--|--|--|
| HP ProCurve 3500-24-PoE Switch (J9471A) | Ports | 20 RJ-45 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Media Type: Auto-MDIX; Duplex: half or full |
| | | 4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) with PoE or an open mini-GBIC slot (for use with mini-GBIC transceivers) |
| | | 1 RS-232C DB-9 console port |
| Physical characteristics | Dimensions | 15.43(d) x 17.44(w) x 1.73(h) in. (39.2 x 44.3 x 4.4 cm) (1U height) |
| | Weight | 13.23 lb. (6 kg) |
| Memory and processor | Management Module | Stackable memory and processor: Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM |
| Mounting | | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only |
| Performance | Latency | 100 Mb: < 3.4 μ s (FIFO 64-byte packets); 1000 Mb: < 2.9 μ s (FIFO 64-byte packets) |
| | Throughput | up to 8.9 million pps (64-byte packets) |
| | Routing/Switching capacity | 12 Gbps |
| | Routing table size | 10,000 entries |
| | MAC address table size | 64,000 entries |
| Environment | Operating temperature | 32°F to 131°F (0°C to 55°C) |
| | Operating relative humidity | 15% to 95% @ 104°F (40°C), non-condensing |
| | Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| | Non-operating/Storage relative humidity | 15% to 95% @ 149°F (65°C), non-condensing |
| | Altitude | up to 15,000 ft. (4.6 km) |
| | Acoustic | Power: 52.7 dB, Pressure: 44.8 dB ISO 7779, ISO 9296 |
| Electrical | Description | The switch automatically adjusts to any |

Technical Specifications

| | |
|------------------------|--|
| characteristics | <p>voltage between 100-127 and 200-240 volts and either 50 or 60 Hz</p> <p>Maximum heat dissipation 435 BTU/hr (458.92 kJ/hr)</p> <p>Voltage 100-127 / 200-240 VAC</p> <p>Current 6.6 / 3.0 A</p> <p>Idle power 91 W</p> <p>Maximum power rating 497 W</p> <p>PoE power 398 W</p> <p>Frequency 50 / 60 Hz</p> <p>Notes Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).</p> |
| Safety | EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950 |
| Emissions | FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A |
| Immunity | <p>EN EN 55024, CISPR 24</p> <p>ESD IEC 61000-4-2; 4 kV CD, 8 kV AD</p> <p>Radiated IEC 61000-4-3; 3 V/m</p> <p>EFT/Burst IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)</p> <p>Surge IEC 61000-4-5; 1 kV/2 kV AC</p> <p>Conducted IEC 61000-4-6; 3 V</p> <p>Power frequency magnetic field IEC 61000-4-8; 1 A/m, 50 or 60 Hz</p> <p>Voltage dips and interruptions IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods</p> <p>Harmonics EN 61000-3-2, IEC 61000-3-2</p> <p>Flicker EN 61000-3-3, IEC 61000-3-3</p> |
| Management | HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C) |
| Notes | When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. |
| Services | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (U2855E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (U2856E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6304E)</p> |

Technical Specifications

3-year, 24x7 SW phone support, software updates (UE262E)
4-year, 4-hour onsite, 13x5 coverage for hardware (UR868E)
4-year, 4-hour onsite, 24x7 coverage for hardware (UR869E)
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR870E)
4-year, 24x7 SW phone support, software updates (UR871E)
5-year, 4-hour onsite, 13x5 coverage for hardware (UR872E)
5-year, 4-hour onsite, 24x7 coverage for hardware (UR873E)
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR874E)
5-year, 24x7 SW phone support, software updates (UR875E)
Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

| | |
|--------------------------|--|
| Device Management | RFC 1591 DNS (client) HTML and telnet management |
| General Protocols | IEEE 802.1ad Q-in-Q (Premium License) IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP UDLD (Uni-directional Link Detection) RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2453 RIPv2 RFC 2548 (MS-RAS-Vendor only) RFC 3046 DHCP Relay Agent Information Option RFC 3576 Ext to RADIUS (CoA only) RFC 3768 VRRP (Premium License) RFC 4675 RADIUS VLAN & Priority |

Technical Specifications

| | |
|---------------------------|---|
| IP Multicast | RFC 3376 IGMPv3 (host joins only) RFC 3973 Draft 2 PIM Dense Mode (Premium License) RFC 4601 Draft 10 PIM Sparse Mode (Premium License) |
| IPv6 | RFC 1981 IPv6 Path MTU Discovery RFC 2460 IPv6 Specification RFC 2710 Multicast Listener Discovery (MLD) for IPv6 RFC 2925 Remote Operations MIB (Ping only) RFC 3019 MLDv1 MIB RFC 3315 DHCPv6 (client only) RFC 3513 IPv6 Addressing Architecture RFC 3596 DNS Extension for IPv6 RFC 3810 MLDv2 (host joins only) RFC 4022 MIB for TCP RFC 4113 MIB for UDP RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication RFC 4253 SSHv6 Transport Layer RFC 4254 SSHv6 Connection RFC 4293 MIB for IP RFC 4419 Key Exchange for SSH RFC 4443 ICMPv6 RFC 4541 IGMP & MLD Snooping Switch RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration |
| MIBs | RFC 1213 MIB II RFC 1493 Bridge MIB RFC 1724 RIPv2 MIB RFC 1850 OSPFv2 MIB RFC 2021 RMONv2 MIB RFC 2096 IP Forwarding Table MIB RFC 2613 SMON MIB RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2737 Entity MIB (Version 2) RFC 2787 VRRP MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB |
| Network Management | IEEE 802.1AB Link Layer Discovery Protocol (LLDP) RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) RFC 3176 sFlow ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3 XRMON |

Technical Specifications

| | |
|-----------------|---|
| OSPF | RFC 2328 OSPFv2 (Premium License) RFC 3101 OSPF NSSA |
| QoS/Cos | RFC 2474 DiffServ Precedence, including 8 queues/port RFC 2597 DiffServ Assured Forwarding (AF) RFC 2598 DiffServ Expedited Forwarding (EF) |
| Security | IEEE 802.1X Port Based Network Access Control RFC 1492 TACACS+ RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting Secure Sockets Layer (SSL) SSHv1/SSHv2 Secure Shell |

| | | |
|--|--|--|
| HP ProCurve 3500-48 Switch (J9472A) | Ports | 44 RJ-45 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Media Type: Auto-MDIX; Duplex: half or full |
| | | 4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) with PoE or an open mini-GBIC slot (for use with mini-GBIC transceivers) |
| Physical characteristics | | 1 RS-232C DB-9 console port |
| | Dimensions | 16.93(d) x 17.44(w) x 1.73(h) in. (43.0 x 44.3 x 4.4 cm) (1U height) |
| | Weight | 13.45 lb. (7.3 kg) |
| Memory and processor | Management Module | Stackable memory and processor: Freescale PowerPC 8540 @ 666 MHz, 4 MB flash Mb, 128 MB compact flash, 256 MB DDR SDRAM |
| Mounting | | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only |
| Performance | Latency | 100 Mb: < 3.4 μs (FIFO 64-byte packets); 1000 Mb: < 2.9 μs (FIFO 64-byte packets) |
| | Throughput | up to 12.5 million pps (64-byte packets) |
| | Routing/Switching capacity | 16.8 Gbps |
| | Routing table size | 10,000 entries |
| | MAC address table size | 64,000 entries |
| Environment | Operating temperature | 32°F to 131°F (0°C to 55°C) |
| | Operating relative humidity | 15% to 95% @ 104°F (40°C), non-condensing |
| | Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| | Non-operating/Storage relative humidity | 15% to 95% @ 149°F (65°C), non-condensing |
| | Altitude | up to 15,000 ft. (4.6 km) |
| | Acoustic | Power: 52 dB, Pressure: 45.3 dB ISO 7779, ISO 9296 |

Technical Specifications

| | | |
|---------------------------------------|--|---|
| Electrical characteristics | Description | The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz |
| | Maximum heat dissipation | 465 BTU/hr (490.58 kJ/hr) |
| | Voltage | 100-127 / 200-240 VAC |
| | Current | 1.6 / 0.8 A |
| | Idle power | 96 W |
| | Maximum power rating | 136.2 W |
| | PoE power | |
| | Frequency | 50 / 60 Hz |
| | Notes | Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| | Safety Emissions Immunity | |
| | | FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A |
| EN | | EN 55024, CISPR 24 |
| ESD | | IEC 61000-4-2; 4 kV CD, 8 kV AD |
| Radiated | | IEC 61000-4-3; 3 V/m |
| EFT/Burst | | IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) |
| Surge | | IEC 61000-4-5; 1 kV/2 kV AC |
| Conducted | | IEC 61000-4-6; 3 V |
| Power frequency magnetic field | | IEC 61000-4-8; 1 A/m, 50 or 60 Hz |
| Voltage dips and interruptions | | IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods |
| Harmonics | | EN 61000-3-2, IEC 61000-3-2 |
| Flicker | | EN 61000-3-3, IEC 61000-3-3 |
| Management | | HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C) |
| Notes | When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. | |
| Services | 3-year, 4-hour onsite, 13x5 coverage for hardware (H4496E) 3-year, 4-hour onsite, 24x7 coverage for hardware (H2893E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6319E) 3-year, 24x7 SW phone support, software updates (UE264E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR884E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR885E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR886E) 4-year, 24x7 SW phone support, software updates (UR887E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR888E) | |

Technical Specifications

5-year, 4-hour onsite, 24x7 coverage for hardware (UR889E)
 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR890E)
 5-year, 24x7 SW phone support, software updates (UR891E)

Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

| | |
|--------------------------|--|
| Device Management | RFC 1591 DNS (client) HTML and telnet management |
| General Protocols | IEEE 802.1ad Q-in-Q (Premium License) IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP UDLD (Uni-directional Link Detection) RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2453 RIPv2 RFC 2548 (MS-RAS-Vendor only) RFC 3046 DHCP Relay Agent Information Option RFC 3576 Ext to RADIUS (CoA only) RFC 3768 VRRP (Premium License) RFC 4675 RADIUS VLAN & Priority |
| IP Multicast | RFC 3376 IGMPv3 (host joins only) RFC 3973 Draft 2 PIM Dense Mode (Premium License) RFC 4601 Draft 10 PIM Sparse Mode (Premium License) |
| IPv6 | RFC 1981 IPv6 Path MTU Discovery RFC 2460 IPv6 Specification RFC 2710 Multicast Listener Discovery (MLD) for IPv6 |

| | |
|---------------------------|---|
| | RFC 2925 Remote Operations MIB (Ping only) |
| | RFC 3019 MLDv1 MIB |
| | RFC 3315 DHCPv6 (client only) |
| | RFC 3513 IPv6 Addressing Architecture |
| | RFC 3596 DNS Extension for IPv6 |
| | RFC 3810 MLDv2 (host joins only) |
| | RFC 4022 MIB for TCP |
| | RFC 4113 MIB for UDP |
| | RFC 4251 SSHv6 Architecture |
| | RFC 4252 SSHv6 Authentication |
| | RFC 4253 SSHv6 Transport Layer |
| | RFC 4254 SSHv6 Connection |
| | RFC 4293 MIB for IP |
| | RFC 4419 Key Exchange for SSH |
| | RFC 4443 ICMPv6 |
| | RFC 4541 IGMP & MLD Snooping Switch |
| | RFC 4861 IPv6 Neighbor Discovery |
| | RFC 4862 IPv6 Stateless Address Auto-configuration |
| MIBs | RFC 1213 MIB II |
| | RFC 1493 Bridge MIB |
| | RFC 1724 RIPv2 MIB |
| | RFC 1850 OSPFv2 MIB |
| | RFC 2021 RMONv2 MIB |
| | RFC 2096 IP Forwarding Table MIB |
| | RFC 2613 SMON MIB |
| | RFC 2618 RADIUS Client MIB |
| | RFC 2620 RADIUS Accounting MIB |
| | RFC 2665 Ethernet-Like-MIB |
| | RFC 2668 802.3 MAU MIB |
| | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| | RFC 2737 Entity MIB (Version 2) |
| | RFC 2787 VRRP MIB |
| | RFC 2863 The Interfaces Group MIB |
| | RFC 2925 Ping MIB |
| Network Management | IEEE 802.1AB Link Layer Discovery Protocol (LLDP) |
| | RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) |
| | RFC 3176 sFlow |
| | ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) |
| | SNMPv1/v2c/v3 |
| | XRMON |
| OSPF | RFC 2328 OSPFv2 (Premium License) |
| | RFC 3101 OSPF NSSA |
| QoS/Cos | RFC 2474 DiffServ Precedence, including 8 queues/port |
| | RFC 2597 DiffServ Assured Forwarding (AF) |
| | RFC 2598 DiffServ Expedited Forwarding (EF) |
| Security | IEEE 802.1X Port Based Network Access Control |
| | RFC 1492 TACACS+ |

Technical Specifications

RFC 2865 RADIUS (client only)
 RFC 2866 RADIUS Accounting Secure
 Sockets Layer (SSL)
 SSHv1/SSHv2 Secure Shell

| | | |
|--|---|---|
| HP ProCurve 3500-48-PoE Switch (J9473A) | Ports | <p>44 RJ-45 auto-sensing 10/100 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Media Type: Auto-MDIX; Duplex: half or full</p> <p>4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) with PoE or an open mini-GBIC slot (for use with mini-GBIC transceivers)</p> <p>1 RS-232C DB-9 console port</p> |
| | Physical characteristics | <p>Dimensions 16.93(d) x 17.44(w) x 1.73(h) in. (43.0 x 44.3 x 4.4 cm) (1U height)</p> <p>Weight 16.09 lb. (7.3 kg)</p> |
| | Memory and processor Management Module | Stackable memory and processor: Freescale PowerPC 8540 @ 666 MHz, 4 MB flash Mb, 128 MB compact flash, 256 MB DDR SDRAM |
| | Mounting | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only |
| | Performance | <p>Latency 100 Mb: < 3.4 μs (FIFO 64-byte packets); 1000 Mb: < 2.9 μs (FIFO 64-byte packets)</p> <p>Throughput up to 12.5 million pps (64-byte packets)</p> <p>Routing/Switching capacity 16.8 Gbps</p> <p>Routing table size 10,000 entries</p> <p>MAC address table size 64,000 entries</p> |
| | Environment | <p>Operating temperature 32°F to 131°F (0°C to 55°C)</p> <p>Operating relative humidity 15% to 95% @ 104°F (40°C), non-condensing</p> <p>Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Non-operating/Storage relative humidity 15% to 95% @ 149°F (65°C), non-condensing</p> <p>Altitude up to 15,000 ft. (4.6 km)</p> <p>Acoustic Power: 55.1 dB, Pressure: 45.3 dB ISO 7779, ISO 9296</p> |
| | Electrical characteristics | <p>Description The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz</p> <p>Maximum heat dissipation 611 BTU/hr (644.6 kJ/hr)</p> <p>Voltage 100-127 / 200-240 VAC</p> <p>Current 7.3 / 3.3 A</p> <p>Idle power 133.2 W</p> <p>Maximum power rating 548.8 W</p> |

Technical Specifications

| | | |
|-------------------|---------------------------------------|---|
| | PoE power | 398 W |
| | Frequency | 50 / 60 Hz |
| | Notes | Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS). |
| Safety | | EN 60950/IEC 60950; CAN/CSA 22.2 No. 60950; EN 60825; UL 60950 |
| Emissions | | FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A |
| Immunity | EN | EN 55024, CISPR 24 |
| | ESD | IEC 61000-4-2; 4 kV CD, 8 kV AD |
| | Radiated | IEC 61000-4-3; 3 V/m |
| | EFT/Burst | IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) |
| | Surge | IEC 61000-4-5; 1 kV/2 kV AC |
| | Conducted | IEC 61000-4-6; 3 V |
| | Power frequency magnetic field | IEC 61000-4-8; 1 A/m, 50 or 60 Hz |
| | Voltage dips and interruptions | IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods |
| | Harmonics | EN 61000-3-2, IEC 61000-3-2 |
| | Flicker | EN 61000-3-3, IEC 61000-3-3 |
| Management | | HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C) |
| Notes | | When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. |
| Services | | 3-year, 4-hour onsite, 13x5 coverage for hardware (H4496E) 3-year, 4-hour onsite, 24x7 coverage for hardware (H2893E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6319E) 3-year, 24x7 SW phone support, software updates (UE264E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR884E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR885E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR886E) 4-year, 24x7 SW phone support, software updates (UR887E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR888E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR889E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR890E) 5-year, 24x7 SW phone support, software updates (UR891E) |

Refer to the HP Web site at www.procurve.com/services for details on

Technical Specifications

the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

| | |
|--------------------------|--|
| Device Management | RFC 1591 DNS (client) HTML and telnet management |
| General Protocols | IEEE 802.1ad Q-in-Q (Premium License) IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP UDLD (Uni-directional Link Detection) RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2453 RIPv2 RFC 2548 (MS-RAS-Vendor only) RFC 3046 DHCP Relay Agent Information Option RFC 3576 Ext to RADIUS (CoA only) RFC 3768 VRRP (Premium License) RFC 4675 RADIUS VLAN & Priority |
| IP Multicast | RFC 3376 IGMPv3 (host joins only) RFC 3973 Draft 2 PIM Dense Mode (Premium License) RFC 4601 Draft 10 PIM Sparse Mode (Premium License) |
| IPv6 | RFC 1981 IPv6 Path MTU Discovery RFC 2460 IPv6 Specification RFC 2710 Multicast Listener Discovery (MLD) for IPv6 RFC 2925 Remote Operations MIB (Ping only) RFC 3019 MLDv1 MIB RFC 3315 DHCPv6 (client only) RFC 3513 IPv6 Addressing Architecture RFC 3596 DNS Extension for IPv6 |

| | |
|---------------------------|---|
| | RFC 3810 MLDv2 (host joins only) |
| | RFC 4022 MIB for TCP |
| | RFC 4113 MIB for UDP |
| | RFC 4251 SSHv6 Architecture |
| | RFC 4252 SSHv6 Authentication |
| | RFC 4253 SSHv6 Transport Layer |
| | RFC 4254 SSHv6 Connection |
| | RFC 4293 MIB for IP |
| | RFC 4419 Key Exchange for SSH |
| | RFC 4443 ICMPv6 |
| | RFC 4541 IGMP & MLD Snooping Switch |
| | RFC 4861 IPv6 Neighbor Discovery |
| | RFC 4862 IPv6 Stateless Address Auto-configuration |
| MIBs | RFC 1213 MIB II |
| | RFC 1493 Bridge MIB |
| | RFC 1724 RIPv2 MIB |
| | RFC 1850 OSPFv2 MIB |
| | RFC 2021 RMONv2 MIB |
| | RFC 2096 IP Forwarding Table MIB |
| | RFC 2613 SMON MIB |
| | RFC 2618 RADIUS Client MIB |
| | RFC 2620 RADIUS Accounting MIB |
| | RFC 2665 Ethernet-Like-MIB |
| | RFC 2668 802.3 MAU MIB |
| | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| | RFC 2737 Entity MIB (Version 2) |
| | RFC 2787 VRRP MIB |
| | RFC 2863 The Interfaces Group MIB |
| | RFC 2925 Ping MIB |
| Network Management | IEEE 802.1AB Link Layer Discovery Protocol (LLDP) |
| | RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) |
| | RFC 3176 sFlow |
| | ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) |
| | SNMPv1/v2c/v3 |
| | XRMON |
| OSPF | RFC 2328 OSPFv2 (Premium License) |
| | RFC 3101 OSPF NSSA |
| QoS/Cos | RFC 2474 DiffServ Precedence, including 8 queues/port |
| | RFC 2597 DiffServ Assured Forwarding (AF) |
| | RFC 2598 DiffServ Expedited Forwarding (EF) |
| Security | IEEE 802.1X Port Based Network Access Control |
| | RFC 1492 TACACS+ |
| | RFC 2865 RADIUS (client only) |
| | RFC 2866 RADIUS Accounting Secure Sockets Layer (SSL) |
| | SSHv1/SSHv2 Secure Shell |

Accessories

| | | |
|---|---|--------|
| HP ProCurve Switch 3500yl Series accessories | Premium License for Switch 3500 Series | J8993A |
| | HP ProCurve 620 Redundant/External Power Supply | J8696A |
| | HP ProCurve 100-FX SFP-LC Transceiver | J9054B |
| | NEW HP ProCurve 100-BX-D SFP-LC Transceiver | J9099B |
| | NEW HP ProCurve 100-BX-U SFP-LC Transceiver | J9100B |
| | HP ProCurve Gigabit-SX-LC Mini-GBIC | J4858C |
| | HP ProCurve Gigabit-LX-LC Mini-GBIC | J4859C |
| | HP ProCurve Gigabit-LH-LC Mini-GBIC | J4860C |
| | NEW HP ProCurve 1000-BX-D SFP-LC Mini-GBIC | J9142B |
| | NEW HP ProCurve 1000-BX-U SFP-LC Mini-GBIC | J9143B |
| | HP ProCurve 10-GbE X2-SC SR Optic | J8436A |
| | NEW HP ProCurve 10-GbE X2-SC LRM Optic | J9144A |
| | HP ProCurve 10-GbE X2-SC LR Optic | J8437A |
| | HP ProCurve 10-GbE X2-SC ER Optic | J8438A |
| | HP ProCurve 10-GbE X2-CX4 Transceiver | J8440B |
| | HP ProCurve 10-GbE CX4 Media Converter | J8439A |
| | HP ProCurve Manager 3.0 | - |

| | | |
|-------------------|--|--------|
| yl Modules | HP ProCurve Switch yl 10-GbE 2-Port CX4 + 2-Port X2 Module | J8694A |
|-------------------|--|--------|

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: www.hp.com/go/procurve
 Information is subject to change without notice